



(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number
WO 02/064677 A2

(51) International Patent Classification: **C08L 53/00**

(US). **HALL, James** [US/US]; 1929 Portage Line Road, Mogadore, OH 44260 (US). **FOLTZ, Victor** [US/US]; 2895 Premae Drive, Akron, OH 44312 (US).

(21) International Application Number: PCT/US02/04562

(22) International Filing Date: 15 February 2002 (15.02.2002)

(74) Agents: **HORNICKEL, John**; Bridgestone/Firestone Americas Holding, Inc., 1200 Firestone Parkway, Akron, OH 44317 et al. (US).

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): CN, JP, US.

(30) Priority Data:
60/269,138 15 February 2001 (15.02.2001) US

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

(71) Applicant (*for all designated States except US*): **BRIDGE-STONE CORPORATION** [JP/JP]; 10-1, Kyobashi 1-Chome, Chuo-Ku, Tokyo 104 (JP).

Published:

— *without international search report and to be republished upon receipt of that report*

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **WANG, Xiaorong** [CN/US]; 5253 Wilshire Park Drive, Hudson, OH 44236

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 02/064677 A2

(54) Title: **SOFT GEL COMPOSITIONS FOR HOT ADHESION**

(57) Abstract: A gel composition that is the combination of or reaction product of ingredients comprising a thermoplastic elastomer copolymer, a functionalized polyolefin, an extender, and optionally a fatty acid.

SOFT GEL COMPOSITIONS FOR HOT ADHESION

This application gains priority from U.S. Patent Application Serial No. 60/269,138 filed on February 15, 2001.

5

BACKGROUND OF THE INVENTION

Disk drive assemblies for computers typically include a magnetic storage disk coaxially mounted about a spindle apparatus that rotates at speeds in excess of several thousand revolutions per minute (RPM). The disk drive assemblies also include a magnetic head that writes and reads information to and from the rotating magnetic storage disk. The magnetic head is usually disposed at the end of an actuator arm and is positioned in a space above the magnetic disk. The actuator arm can move relative to the magnetic disk. The disk drive assembly is mounted on a disk base (support) plate and sealed with a cover plate to form a housing that protects the disk drive assembly from contamination.

15

Serious damage to the magnetic disks, including loss of valuable information, can result from gaseous and particulate contaminants in the disk drive assembly housing. To prevent or substantially reduce introduction of such contaminants into the disk drive housing, a flexible sealing gasket is disposed between the mounting plate and the cover plate. The sealing gaskets typically are prepared by punching annular disks from a sheet of cured elastomer.

20

Such gaskets typically are adhered or mechanically attached, e.g., affixed with screws, to the support plate. Being able to eliminate these types of separate chemical or mechanical attachment means by providing a self-securing gasket would be highly desirable.

25

SUMMARY OF THE INVENTION

In general the present invention provides a gel composition that is the combination of or reaction product of ingredients comprising a thermoplastic elastomer copolymer, a functionalized polyolefin, an extender, and optionally a fatty acid.

30

The present invention also includes a gasket formed by melt extruding a composition that is the combination or reaction product of ingredients

comprising a thermoplastic elastomer copolymer, a functionalized polyolefin, an extender, and optionally a fatty acid.

5 The present invention further provides a disk drive assembly for computers comprising a gasket formed by melt extruding a composition that is the combination or reaction product of ingredients comprising a thermoplastic elastomer copolymer, a functionalized polyolefin, an extender, and optionally a fatty acid.

10 The soft gel compositions of this invention are advantageously thermoreversible, and therefore they can be applied by hot injection molding or melt extruding. Also, these compositions can be recycled. Further, the unique combination of materials employed within the composition provides for a material that has excellent adhesive characteristics, especially to metals and plastics, and very low gas permeability. Accordingly, gaskets made from the composition of this invention can be directly applied to a metal or plastic surface via heat molding.
15 The gaskets advantageously greatly reduce the intrusion of gases and airborne contaminants into devices such as disk drive assemblies.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

20 The gel compositions include a blend of a thermoplastic elastomer copolymer, a functionalized polyolefin, an extender, and, optionally, a fatty acid. These compositions are soft and thermoreversible gels that have been found to exhibit good hot adhesion to metal and plastic substrates.

Useful thermoplastic elastomer copolymers include, but are not limited to, styrene/butadiene rubber (SBR), styrene/isoprene rubber (SIR),
25 styrene/isoprene/butadiene rubber (SIBR), styrene-butadiene-styrene block copolymer (SBS), hydrogenated styrene-butadiene-styrene block copolymer (SEBS), hydrogenated styrene-butadiene block copolymer (SEB), styrene-isoprene-styrene block copolymer (SIS), styrene-isoprene block copolymer (SI), hydrogenated styrene-isoprene block copolymer (SEP), hydrogenated styrene-
30 isoprene-styrene block copolymer (SEPS), styrene-ethylene/butylene-ethylene block copolymer (SEBE), styrene-ethylene-styrene block copolymer (SES), ethylene-ethylene/butylene block copolymer (EEB), ethylene-ethylene/butylene/styrene block copolymer (hydrogenated BR-SBR block

copolymer), styrene-ethylene/butylene-ethylene block copolymer (SEBE), ethylene-ethylene/butylene-ethylene block copolymer (EEBE) and mixtures thereof.

Preferred copolymers include hydrogenated styrene-butadiene-
5 styrene block copolymer (SEBS) and hydrogenated styrene-isoprene-styrene block copolymer (SEPS). The preferred copolymers are commercially available under the tradename SEPTON (Kuraray; New York, New York). A hydrogenated block copolymer can be obtained by hydrogenating a block copolymer that includes at least two polymer blocks A composed mainly of a vinyl-substituted aromatic
10 hydrocarbon and at least one polymer block B composed mainly of a conjugated diene, where "composed mainly of" refers to a plurality of the mer units of the polymer or segment resulting from the polymerization of the indicated monomer.

The hydrogenated block copolymer can have a polymer structure represented by such formulae as, for example, $(A-B)_nA$, $(B-A-B)_nA$, $(B-A-B)_nA-B$,
15 $(A-B)_mX$, $(B-A-B)_mX$, etc., where n is an integer of 1 or more, m is an integer of 2 or more, and X represents a coupling or polyfunctional initiator residue having two or more functional groups.

The hydrogenated block copolymer can compose from about 5 to 60 wt. %, preferably 10 to 50 wt. %, of a vinyl-substituted aromatic hydrocarbon.
20 Polymer block A, composed mainly of a vinyl-substituted aromatic hydrocarbon, has the structure of a homopolymer block of a vinyl-substituted aromatic hydrocarbon or a copolymer block of a vinyl-substituted aromatic hydrocarbon containing more than 50 wt. %, and preferably not less than 70 wt. %, of vinyl-substituted aromatic hydrocarbon with a hydrogenated conjugated diene. Polymer
25 block B, composed mainly of a hydrogenated conjugated diene, has the structure of a homopolymer block of a hydrogenated conjugated diene or a copolymer block of a hydrogenated conjugated diene containing more than 50 wt. %, and preferably not less than 70 wt. %, of hydrogenated conjugated diene with a vinyl-substituted aromatic hydrocarbon. Also, as to the distribution of the hydrogenated conjugated
30 diene or the vinyl-substituted aromatic hydrocarbon contained in the molecular chains of blocks A and B, both polymer blocks may take any of random, tapered (the monomer components increase or decrease along the molecular chain) and

partial block arrangements and, when the numbers of either of both of blocks A and B are 2 or more, the structures of the respective individual blocks may be the same or different.

5 The hydrogenated block copolymer, in one embodiment, has a number average molecular weight (M_n) of about 100,000 to about 1,000,000, preferably about 125,000 to about 800,000, more preferably about 150,000 to about 500,000. The molecular weight distribution (M_w/M_n) is preferably 10 or less. The molecular structure type of the hydrogenated block copolymer may be selected from straight-chain, branched-chained involving partial coupling with a
10 coupling agent, radial, and the star-shaped types and combinations thereof.

Hydrogenated block copolymers can be obtained by synthesizing a vinyl-substituted aromatic hydrocarbon/conjugated diene block copolymer in an inert solvent using an organo-lithium and if necessary, a 1,2-vinyl bond modifier such as ether compounds, tertiary amines, etc., (See, e.g., British Patent No.
15 1,130,770 and U.S. Patent Nos. 3,281,383 and 3,639,517) and then hydrogenating the resulting block copolymer (See, e.g., British Patent No. 1,020,720 and U.S. Patent Nos. 3,333,024 and 4,501,857). The polymer block composed mainly of the conjugated diene can be changed in form to the polymer block of an olefinic compound by hydrogenating at least 80 mole % of the aliphatic double bonds
20 coming from the conjugated diene of the vinyl-substituted aromatic hydrocarbon/conjugated diene block copolymer.

Also, although the hydrogenation ratio of the aromatic double bond coming from polymer block A and/or the vinyl-substituted aromatic hydrocarbon incorporated as a co-monomer, as need arises, in the polymer block B is not
25 critical, it preferably is 20 mole % or less.

The functionalized polyolefin additive includes an α -olefin polymer that contains terminal or pendent moieties containing acid, anhydride, hydroxyl, imide, amine or amide groups.

30 The terminal or pendent moieties preferably derive from unsaturated carboxylic acids or unsaturated anhydrides. Examples of unsaturated carboxylic acids include citraconic acid, cinnamic acid, methacrylic acid, and itaconic acid. Examples of unsaturated anhydrides include maleic anhydride, citraconic

anhydride, and itaconic anhydride. The preferred terminal or pendent moieties are succinic anhydride groups, or the corresponding acid from a ring opening structure, that derives from maleic anhydride.

5 The α -olefin polymer includes an α -olefin homopolymer, a copolymer of two or more α -olefins, or a copolymer of an α -olefin with a compatible monomer. The α -olefins can include from about 2 to about 8 carbon atoms, and more preferably from 3 to about 5 carbon atoms. Exemplary α -olefin monomers include ethylene, propylene, butene-1, and pentene-1. Exemplary monomers that can be copolymerized with α -olefins include vinyl aromatic monomers and diene
10 monomers. An exemplary copolymer is poly(propylene-co-ethylene) that contains polyethylene crystals.

The functionalized polyolefins should contain from about 0.01 to about 3 Parts by weight (pbw) of the functional moiety based upon the weight of the entire polymer. More preferably, the modified polyolefin should contain from
15 about 0.1 to about 2 pbw of the functional moiety, an even more preferably from about 0.15 to about 1.0 pbw of the functional moiety.

The weight average molecular weight of the functionalized polyolefins can vary greatly, although it is preferred that the weight average molecular
20 (M_w) be from about 1,000 to about 500,000, more preferably from about 1,500 to about 100,000, even more preferably from about 2,000 to about 50,000, and still more preferably about 3,000 as determined by using standard GPC analysis with polystyrene as a standard. Preferably, the molecular weight distribution (M_w/M_n) should be less than about 4.5, preferably less than about 4.0, and even more
25 preferably less than about 3.8.

The functionalized polyolefin additives are typically prepared by grafting unsaturated carboxylic acids or unsaturated anhydrides to a polyolefin polymer.

30 The techniques employed to attach the terminal or pendent moieties that contain carboxylic acid or anhydride groups to a polyolefin polymer are well known in the art. For example, grafting maleic anhydride to a polyolefin is disclosed in U.S. Patent No. 6,046,279, which is incorporated herein by reference.

The α -olefin polymers can be synthesized by using a number of polymerization techniques such as, but not limited to, the "Phillips catalyzed reactions" conventional Ziegler-Natta type polymerizations, and metallocene catalysis including, but not limited to, metallocene-aluminoxane and metallocene-ionic activator catalysis.

Exemplary α -olefin polymers include polyethylene, polypropylene, poly(ethylene-co-propylene), poly(propylene-co-butene-1), and poly(butene-1-co-ethylene). These α -olefin polymers can be either amorphous, semi-crystalline, or crystalline polymers. The preferred polyolefins include crystalline or stereoregular polypropylene. Most polypropylene homopolymers that are commercially produced have an isotactic microstructure. The poly(propylene-co-ethylene) copolymers can be random or block copolymers. Preferably, these copolymers will contain some polyethylene crystals, although they should include a major amount of propylene units and only a minor amount of ethylene units. Preferably, these copolymers should contain less than about 40 percent by weight (pbw) ethylene units, more preferably from about 1 to about 30 pbw ethylene units, and more preferably from about 1.5 to about 25 pbw ethylene units.

Functionalized polyolefins are commercially available. For example, maleic anhydride functionalized polypropylene is available under the tradename EXXELOR™ PO1015 & 1020 (Exxon Mobil Chemical Company; Houston, Texas), under the tradename PP-C™, CA1000, or 18707 (Elf Atochem; Philadelphia, Pennsylvania), or under the tradename Polybond™ 3001, 3002, or 3150 (Uniroyal Chemical Company; Middlebury, Connecticut).

Useful extenders include oils or low molecular weight organic compounds. Without intending to be bound to any particular theory, the extender is believed to interact with the thermoplastic elastomer copolymer and increase the distance between the thermoplastic blocks or domains thereof, thereby forming an extended or soft gel composition.

Suitable oils include naphthenic, aromatic, paraffinic, phthalic, and silicone oils. A preferred extender oil is paraffinic oil. Preferably, the extender oils have a M_w from about 100 to about 10,000.

Examples of low molecular weight organic compounds include organic materials having a M_n of less than 20,000, preferably less than 10,000, and most preferably less than 5,000. Suitable low molecular weight compounds include softening agents, plasticizers, oligomers, liquid polymers and copolymers, lubricants, and low molecular weight petroleum products. Other appropriate low-molecular organic materials include latexes, emulsions, liquid crystals, bituminous compositions, and phosphazenes. One or more of these materials may be used as extenders.

Exemplary softening agents include aromatic, naphthenic, and paraffinic softening agents, which are commonly used in rubbers or resins.

Exemplary plasticizers include phthalic esters, mixed phthalic esters, aliphatic dibasic acid esters, glycol esters, fatty acid esters, phosphoric esters, stearic esters, epoxy esters, phthalate esters, adipate esters, sebacate esters, phosphate esters, polyether and polyester plasticizers, which are commonly used with nitrile rubber.

Exemplary tackifiers include coumarone resins, coumarone-indene resins, terpene phenol resins, petroleum hydrocarbons, and rosin derivatives.

Exemplary oligomers include crown ether, fluorine-containing oligomers, polybutenes, xylene resins, chlorinated rubber, polyethylene wax, petroleum resins, rosin ester rubber, polyalkylene glycol diacrylate, liquid rubber (polybutadiene, styrene/butadiene rubber, butadiene-acrylonitrile rubber, polychloroprene, etc.), silicone oligomers, and poly- α -olefins.

Exemplary lubricants include hydrocarbon lubricants such as paraffins and waxes, fatty acid lubricants such as higher fatty acids and hydroxy-fatty acids, fatty acid amide lubricants such as fatty acid amides and alkylene-bis-fatty acid amides, ester lubricants such as fatty acid-lower alcohol esters, fatty acid-polyhydric alcohol esters and fatty acid-polyglycol esters, alcoholic lubricants such as fatty alcohols, polyhydric alcohols, polyglycols and polyglycerols, metallic soaps, and mixed lubricants.

Exemplary petroleum products include synthetic terpene resins, aromatic hydrocarbon resins, aliphatic hydrocarbon resins, aliphatic cyclic hydrocarbon resins, aliphatic or alicyclic petroleum resins, aliphatic or aromatic

petroleum resins, polymers of unsaturated hydrocarbons, and hydrogenated hydrocarbon resins.

The gel compositions may optionally include a fatty acid, particularly a mono-functional, di-functional, and multi-functional fatty acid. Preferred fatty acids have 1 to about 60 carbon atoms, more preferably about 3 to about 40 carbon atoms, and more preferably about 5 to about 20 carbon atoms.

Suitable fatty acids include mono-functional fatty acids such as octanoic acid, nonanoic acid, decanoic acid, lauric acid, myristic acid, palmitic acid, and stearic acid, and di-functional fatty acids such as suberic acid, sebacic acid, dodecandioic acid, hexadecane-dioic acid, and 5-(octadecyloxy)isophthalic acid.

The fatty acid preferably has attached thereto 1 to about 10, more preferably from about 1 to about 5, and most preferably from about 1 to about 4 carboxyl groups. Mono-functional fatty acids, such as stearic acid, are particularly preferred.

The gel composition may also include other additives such as, for example, fillers, shrinkage inhibiting agents, and pigments.

Suitable fillers include both organic and inorganic fillers. Preferred organic fillers include carbon black. Preferred inorganic fillers include silica, alumina, aluminum hydroxide, magnesium hydroxide, and various clays. Fillers are typically employed in amount from about 5 to about 30 pbw per 100 pbw of thermoplastic elastomer.

Useful shrinkage inhibiting agents include crystalline polyolefins. Suitable crystalline polyolefins include polyethylene and polypropylene. Crystalline polyolefins are typically used in amount from about 5 to about 20 pbw per 100 pbw of thermoplastic elastomer copolymer.

The gel compositions preferably include about 1 to about 100 pbw functionalized polyolefin, about 1 to about 1,000 pbw extender, and 0 to about 100 pbw fatty acid per 100 pbw thermoplastic elastomer copolymer. More preferably, the gel compositions include about 10 to about 90 pbw functionalized polyolefin, about 50 to about 500 pbw extender, and about 5 to about 50 pbw fatty acid per 100 pbw thermoplastic elastomer copolymer. Even more preferably, the gel compositions include about 50 to about 80 pbw functionalized polyolefin,

about 200 to about 400 pbw extender, and about 15 to about 40 pbw fatty acid per 100 pbw thermoplastic elastomer copolymer.

The soft gel compositions are formed by combining or mixing the thermoplastic elastomer copolymer, functionalized polyolefin, extender, and optional fatty acid. The extender is preferably added during final processing. While the soft gel composition is believed to result from the mere combination of these components, the degree of interaction or reaction between the various components is not known with any great degree of certainty. The term soft gel composition, therefore, is intended to encompass a simple mixture or blend of the components, a complex of the three components that results from physical or chemical forces of attraction, a chemical reaction products of the components, or a combination of the foregoing.

Solid state mixing of the ingredients may be performed in an internal or external mixer. Mixing may also be conducted in solution with an appropriate solvent. Useful solvents include organic solvents, preferably hydrocarbon solvents, and most preferably aliphatic solvents. Solid state mixing can occur at a temperature from about 100° to about 250°C, preferably from about 140° to about 230°C, and more preferably from about 150° to about 200°C.

Once prepared, the soft gel compositions of this invention are thermoreversible and therefore may be employed to produce various articles via melt extruding or injection molding. This extrusion or molding preferably occurs at a temperature from about 160 to about 250 °C.

The soft gel compositions preferably have a Shore A hardness of less than about 35. They exhibit excellent thermostability, as evidenced by a compression set at 100°C of less than about 60.

The gel composition and articles made therefrom exhibit excellent adhesion to metal and plastic substrates under the conditions of quick hot contact. The adhesion of the gel composition to metal and plastic surfaces eliminates the need for an adhesive to adhere the material to the substrate. In addition, the soft gel composition can be recycled and reused.

Because of its propensity to strongly adhere to metal and plastic surfaces, the gel composition can be utilized to prepare gaskets for disk drives, CD-

ROM drives, DVD-ROM drives for microcomputers, gaskets for cellular telephones and the like. For example, a mounting plate for a disk drive assembly may include a substrate with a sealing gasket adhered thereto, with the sealing gasket being prepared from the gel composition of this invention.

5 The gel composition can be formed into a sealing gasket of any desired shape and easily attached to a base support plate via direct injection molding. These sealing gaskets have improved hardness, tensile strength, compression set, and excellent thermostability and flexibility. They also substantially prevent the introduction of gaseous and particulate contaminants into
10 the disk drive housing.

 Sealing gaskets made from the extended gel composition exhibit excellent adhesion to metal and plastic surfaces. In particular, the sealing gaskets show excellent adhesion to metal substrates such as, but not limited to, aluminum, iron, copper, and nickel surfaces. The gaskets also exhibit particularly good
15 adhesion to nickel-coated metal surfaces such as, but not limited to, nickel-coated aluminum substrates.

 The sealing gaskets made from of the inventive soft gel compositions are self-adhering or self-securing to metal and plastic surfaces under conditions of hot direct injection molding, and thereby eliminate the need for expensive
20 machining of holes, interlocking recesses, or continuous grooves in the base support plate, which are used to secure the sealing gasket to the substrate. The sealing gasket material may be stripped from the surface of a base support plate and the soft gel composition recycled for further use.

 In order to demonstrate the practice of the present invention, the
25 following examples have been prepared and tested. The examples should not, however, be viewed as limiting the scope of the invention. The claims will serve to define the invention.

EXAMPLES

Example 1 (Comparative)

30 A mixture of 52.5 g SEPS and 162.5 g paraffin oil was allowed to sit for about 30 minutes in an aluminum pan at room temperature (23°C). This was charged into a 300 g capacity Brabender mixer equipped with a Banbury blade and

N₂ purging. The mixer was initially set at 180°C and 60 RPM. After 20 minutes of mixing, agitation was terminated and the mixture was removed from the mixer.

The resulting soft gel exhibited a high compression set and a low Shore A hardness but did not adhere to either aluminum or plastic surfaces.

5

Example 2 (Comparative)

A 35 g sample of polypropylene was added to the mixer from Comparative Example 1, which was initially set to 180°C and 60 RPM. After 5 minutes of mixing, the mixture from Comparative Example 1 above was added slowly to the mixer over a period of 5 minutes and mixed for an additional 10 minutes.

10

The resulting soft gel exhibited an improved compression set, Shore A hardness, and tensile strength relative to Comparative Example 1. However, it did not adhere to either aluminum or plastic surfaces.

15

Example 3

A 35 g sample of maleated polypropylene (ELF AtoChem) was added to the same mixer as described in Comparative Example 1, which was initially set as before. After 5 minutes of mixing, the mixture from Comparative Example 1 was added slowly to the mixer over a period of 5 minutes and mixed for an additional 10 minutes.

20

Example 4

Example 3 was repeated except that the maleated polypropylene used was obtained from another source (Sanyo Chem.; Japan).

25

Example 5

Example 4 was repeated except that, after the mixing, 12.5 g stearic acid (Aldrich Chemical Co.; Milwaukee, Wisconsin) was added to the mixer, and the material was mixed for an additional 4 minutes prior to removal.

30

Example 6

Example 5 was repeated except that 12.5 g 1,12-dodecanedicarboxylic was used instead of stearic acid.

Example 7

The gels of Examples 1-6 were molded into sheets and cylinder buttons at about 180°C. Ring samples were cut from the sheets for tensile measurements. The cylinder buttons were used for compression set measurements.

The peel test was carried out on aluminum and metallized polyester surfaces using standard test procedures. Specimens for the peel tests were prepared from sandwiching a compound between two aluminum or two metallized polyester films for 5 minutes at 160°C and a pressure of about 34.5 MPa. The results of the tensile measurements, compression set measurements, and peel tests are shown in the following table.

Table I

	1	2	3	4	5	6
Compression Set at 100°C (%)	73.7	50.1	55.9	50.3	62.0	60.2
Tensile Strength at break (MPa)	1.05	2.67	1.37	1.08	1.32	0.88
Elongation at Break (%)	1214	707	601	739	734	591
Shore A Hardness	4	35	27	20	25	19
Peel load on Al, (N over 2.54 cm)						
Maximum	2.32	1.10	11.8	5.44	7.55	5.05
Average	1.66	0.40	8.24	4.56	5.13	4.23
Peel load on MP*, (N over 2.54 cm)						
Maximum	2.35	0.60	0.97	3.32	9.68	4.91
Average	1.43	0.37	0.69	2.73	7.07	4.35

*MP = metallized polyester

The extended gel compositions of Examples 3-6 were soft, thermoreversible gels.

As shown by Examples 3 and 4, addition of maleated-polypropylene to SEPS improves the tensile strength and hardness of the gel compositions, as compared to those compositions not containing functionalized polyolefin. Additionally, the gel compositions of Examples 3 and 4 exhibited excellent adhesion to aluminum surfaces.

In Example 5, the gel composition included a mono-functional fatty acid, namely stearic acid. In Example 6, the gel composition included a di-functional fatty acid, namely 12-dodecanedicarboxylic acid. These gel compositions exhibited good adhesion to both aluminum and plastic surfaces.

Various modifications and alterations that do not depart from the scope and spirit of this invention will become apparent to those skilled in the art. This invention is not to be duly limited to the illustrative embodiments set forth herein.

CLAIMS

What is claimed is:

1. A gel composition that is the combination of or reaction product of ingredients comprising:

- 5 a thermoplastic elastomer copolymer;
 a functionalized polyolefin;
 an extender; and optionally
 a fatty acid.

10 2. A gasket formed by melt extruding a composition that is the combination or reaction product of ingredients comprising:

- a thermoplastic elastomer copolymer;
 a functionalized polyolefin;
 an extender, and optionally a fatty acid.

15

3. A disk drive assembly for computers comprising a gasket formed by melt extruding a composition that is the combination or reaction product of ingredients comprising:

- a thermoplastic elastomer copolymer;
20 a functionalized polyolefin;
 an extender, and optionally a fatty acid.

25

4. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the ingredients comprise about 1 to about 100 parts by weight of said functionalized polyolefin per 100 parts by weight of said thermoplastic elastomer copolymer, from about 1 to about 1,000 parts by weight of said extender per 100 parts by weight of said thermoplastic elastomer, and about 5 to about 100 parts by weight of said fatty acid per 100 parts by weight of said thermoplastic elastomer.

30

5. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the ingredients comprise about 10 to about 90 parts by weight of said functionalized polyolefin per 100 parts by weight of said thermoplastic

elastomer copolymer, from about 50 to about 500 parts by weight of said extender per 100 parts by weight of said thermoplastic elastomer, and about 5 to about 50 parts by weight of said fatty acid per 100 parts by weight of said thermoplastic elastomer.

5

6. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where said extender is an oil or low molecular weight organic compound.

10

7. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where said thermoplastic elastomer copolymer is a styrene-ethylene/butylene-styrene copolymer, a styrene-ethylene/propylene-styrene copolymer, or mixture thereof.

15

8. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where said fatty acid includes a multi-functional fatty acid.

20

9. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the gel composition is formed by mixing said thermoplastic elastomer copolymer, said functionalized polyolefin, said extender, and said fatty acid in the solid state.

25

10. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the ingredients comprise styrene-ethylene/propylene-styrene copolymer, maleated polypropylene, paraffin oil, and 1,12-dodecanedicarboxylic acid or stearic acid.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number
WO 02/064677 A3

- (51) International Patent Classification?: C08L 53/00, 53/02 (74) Agents: HORNICKEL, John; Bridgestone/Firestone Americas Holding, Inc., 1200 Firestone Parkway, Akron, OH 44317 et al. (US).
- (21) International Application Number: PCT/US02/04562 (81) Designated States (*national*): CN, JP, US.
- (22) International Filing Date: 15 February 2002 (15.02.2002) (84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/269,138 15 February 2001 (15.02.2001) US
Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- (71) Applicant (*for all designated States except US*): BRIDGE-STONE CORPORATION [JP/JP]; 10-1, Kyobashi 1-Chome, Chuo-Ku, Tokyo 104 (JP).
- (72) Inventors; and (88) Date of publication of the international search report:
19 December 2002
- (75) Inventors/Applicants (*for US only*): WANG, Xiaorong [CN/US]; 5253 Wilshire Park Drive, Hudson, OH 44236 (US). HALL, James [US/US]; 1929 Portage Line Road, Mogadore, OH 44260 (US). FOLTZ, Victor [US/US]; 2895 Premae Drive, Akron, OH 44312 (US).
For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SOFT GEL COMPOSITIONS FOR HOT ADHESION

(57) Abstract: A gel composition that is the combination of or reaction product of ingredients comprising a thermoplastic elastomer copolymer, a functionalized polyolefin, an extender, and optionally a fatty acid.

WO 02/064677 A3

INTERNATIONAL SEARCH REPORT

In ☐ National Application No
PCT/US 02/04562

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 C08L53/00 C08L53/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 C08L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 879 832 A (BRIDGESTONE CORP) 25 November 1998 (1998-11-25) whole document	1-10
X	EP 0 879 831 A (BRIDGESTONE CORP) 25 November 1998 (1998-11-25) whole document	1-10
X	EP 0 955 329 A (BRIDGESTONE CORP) 10 November 1999 (1999-11-10) whole document	1-10
X	EP 0 955 319 A (BRIDGESTONE CORP) 10 November 1999 (1999-11-10) whole document	1-10
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

25 September 2002

Date of mailing of the international search report

07/10/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5816 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gold, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 02/04562

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 910 540 A (TAKAHASHI HIDEKI) 8 June 1999 (1999-06-08) whole document -----	1-10

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 02/04562

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0879832	A	25-11-1998	US	5910530 A	08-06-1999
			CA	2237502 A1	19-11-1998
			EP	0879832 A1	25-11-1998
			JP	10316831 A	02-12-1998
EP 0879831	A	25-11-1998	US	5912296 A	15-06-1999
			CA	2237453 A1	19-11-1998
			EP	0879831 A1	25-11-1998
			JP	10316812 A	02-12-1998
EP 0955329	A	10-11-1999	US	6054532 A	25-04-2000
			EP	0955329 A1	10-11-1999
			JP	11343320 A	14-12-1999
EP 0955319	A	10-11-1999	US	6204354 B1	20-03-2001
			EP	0955319 A1	10-11-1999
			JP	11343345 A	14-12-1999
US 5910540	A	08-06-1999	JP	9124887 A	13-05-1997
			DE	19645727 A1	07-05-1997

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 August 2002 (22.08.2002)

PCT

(10) International Publication Number
WO 02/064677 A3

(51) International Patent Classification⁷: C08L 53/00, 53/02

(74) Agents: **HORNICKEL, John**; Bridgestone/Firestone Americas Holding, Inc., 1200 Firestone Parkway, Akron, OH 44317 et al. (US).

(21) International Application Number: PCT/US02/04562

(22) International Filing Date: 15 February 2002 (15.02.2002)

(81) Designated States (*national*): CN, JP, US.

(25) Filing Language: English

(84) Designated States (*regional*): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).

(26) Publication Language: English

(30) Priority Data:
60/269,138 15 February 2001 (15.02.2001) US

Published:
— with international search report
— with amended claims

(71) Applicant (*for all designated States except US*): **BRIDGE-STONE CORPORATION** [JP/JP]; 10-1, Kyobashi 1-Chome, Chuo-Ku, Tokyo 104 (JP).

(88) Date of publication of the international search report:
19 December 2002

(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **WANG, Xiaorong** [CN/US]; 5253 Wilshire Park Drive, Hudson, OH 44236 (US). **HALL, James** [US/US]; 1929 Portage Line Road, Mogadore, OH 44260 (US). **FOLTZ, Victor** [US/US]; 2895 Premae Drive, Akron, OH 44312 (US).

Date of publication of the amended claims: 13 February 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 02/064677 A3

(54) Title: SOFT GEL COMPOSITIONS FOR HOT ADHESION

(57) Abstract: A gel composition that is the combination of or reaction product of ingredients comprising a thermoplastic elastomer copolymer, a functionalized polyolefin, an extender, and optionally a fatty acid.

AMENDED CLAIMS

[received by the International Bureau on 6 December 2002 (06.12.02);
original claims 1-10 amended (4 pages)]

1. A gel composition that is the combination of or reaction product of ingredients comprising:

- 5 a thermoplastic elastomer copolymer selected from the group consisting of styrene/butadiene rubber (SBR), styrene/isoprene rubber (SIR), styrene/isoprene/butadiene rubber (SIBR), styrene-butadiene-styrene block copolymer (SBS), hydrogenated styrene-butadiene-styrene block copolymer (SEBS), hydrogenated styrene-butadiene block copolymer (SEB),
10 styrene-isoprene-styrene block copolymer (SIS), styrene-isoprene block copolymer (SI), hydrogenated styrene-isoprene block copolymer (SEP), hydrogenated styrene-isoprene-styrene block copolymer (SEPS), styrene-ethylene-butylene-ethylene block copolymer (SEBE), styrene-ethylene-styrene block copolymer (SES), ethylene-ethylene-butylene block copolymer (EEB), ethylene-ethylene-butylene/styrene block copolymer (hydrogenated
15 BR-SBR block copolymer), styrene-ethylene-butylene-ethylene block copolymer (SEBE), styrene-ethylene/propylene-styrene copolymer, ethylene-ethylene-butylene-ethylene block copolymer (EEBE) or mixtures thereof;
- 20 a functionalized polyolefin;
an extender; and optionally
a fatty acid.

2. A gasket formed by melt extruding a composition that is the combination or
25 reaction product of ingredients comprising:

- a thermoplastic elastomer copolymer selected from the group consisting of styrene/butadiene rubber (SBR), styrene/isoprene rubber (SIR), styrene/isoprene/butadiene rubber (SIBR), styrene-butadiene-styrene block copolymer (SBS), hydrogenated styrene-butadiene-styrene block copolymer (SEBS), hydrogenated styrene-butadiene block copolymer (SEB),
30 styrene-isoprene-styrene block copolymer (SIS), styrene-isoprene block copolymer (SI), hydrogenated styrene-isoprene block copolymer (SEP), hydrogenated styrene-isoprene-styrene block copolymer (SEPS), styrene-

ethylene/butylene-ethylene block copolymer (SEBE), styrene-ethylene-styrene block copolymer (SES), ethylene-ethylene/butylene block copolymer (EEB), ethylene-ethylene/butylene/styrene block copolymer (hydrogenated BR-SBR block copolymer), styrene-ethylene/butylene-ethylene block copolymer (SEBE), styrene-ethylene/propylene-styrene copolymer, ethylene-ethylene/butylene-ethylene block copolymer (EEBE) or mixtures thereof;

a functionalized polyolefin;

an extender, and optionally a fatty acid.

3. A disk drive assembly for computers comprising a gasket formed by melt extruding a composition that is the combination or reaction product of ingredients comprising:

a thermoplastic elastomer copolymer selected from the group consisting of styrene/butadiene rubber (SBR), styrene/isoprene rubber (SIR), styrene/isoprene/butadiene rubber (SIBR), styrene-butadiene-styrene block copolymer (SBS), hydrogenated styrene-butadiene-styrene block copolymer (SEBS), hydrogenated styrene-butadiene block copolymer (SEB), styrene-isoprene-styrene block copolymer (SIS), styrene-isoprene block copolymer (SI), hydrogenated styrene-isoprene block copolymer (SEP), hydrogenated styrene-isoprene-styrene block copolymer (SEPS), styrene-ethylene/butylene-ethylene block copolymer (SEBE), styrene-ethylene-styrene block copolymer (SES), ethylene-ethylene/butylene block copolymer (EEB), ethylene-ethylene/butylene/styrene block copolymer (hydrogenated BR-SBR block copolymer), styrene-ethylene/butylene-ethylene block copolymer (SEBE), styrene-ethylene/propylene-styrene copolymer, ethylene-ethylene/butylene-ethylene block copolymer (EEBE) or mixtures thereof;

a functionalized polyolefin;

an extender, and optionally a fatty acid.

4. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the ingredients comprise about 1 to about 100 parts by weight of

said functionalized polyolefin per 100 parts by weight of said thermoplastic elastomer copolymer, from about 1 to about 1,000 parts by weight of said extender per 100 parts by weight of said thermoplastic elastomer, and about 5 to about 100 parts by weight of said fatty acid per 100 parts by weight of said thermoplastic elastomer.

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

5. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the ingredients comprise about 10 to about 90 parts by weight of said functionalized polyolefin per 100 parts by weight of said thermoplastic elastomer copolymer, from about 50 to about 500 parts by weight of said extender per 100 parts by weight of said thermoplastic elastomer, and about 5 to about 50 parts by weight of said fatty acid per 100 parts by weight of said thermoplastic elastomer.

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

6. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where said extender is an oil or low molecular weight organic compound.

20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

7. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where said thermoplastic elastomer copolymer is a styrene-ethylene/butylene-styrene copolymer, a styrene-ethylene/propylene-styrene copolymer, or mixture thereof.

25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

8. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where said fatty acid includes a multi-functional fatty acid.

30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

9. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the gel composition is formed by mixing said thermoplastic elastomer copolymer, said functionalized polyolefin, said extender, and said fatty acid in the solid state.

10. The composition of claim 1, the gasket of claim 2, or the disk drive assembly of claim 3, where the ingredients comprise styrene-ethylene/propylene-styrene

copolymer, maleated polypropylene, paraffin oil, and 1,12-dodecanedicarboxylic acid or stearic acid.